

# Discs harrows SR-23 (Rear wheels)



## Standard equipment:

- › Separation between discs SR-23: 23 cm.
- › Models with tubular rectangular chassis (200x100x8 mm).
- › Eccentric shot.
- › Hydraulic system for the actuation of the opening or closing of the harrow cloths and the rear equipment of pneumatic wheels.
- › Rolling system with self-aligning monobloc housings with ball bearings protected by triple-sealed seals that SIMPLIFY THE NECESSITY OF LUBRICATION.
- › Solid steel frame axle (F-114) of 40x40 mm for all models.
- › Standard simple discs.

CODE	MODEL	DISCS				TIRES	WIDTH (m)		WEIGHT (Kg)	POWER (CV)
		Núm.	Supports	Diameter	Separation		Work	Transport		
1011060001	SR-23-14-24	14	4	24" - 61	230 mm.	6.00-16" (8PR)	1,54	1,78	1.060	60-65
1011060002	SR-23-14-26	14	4	26" - 66	230 mm.	6.00-16" (8PR)	1,54	1,78	1.145	60-65
1011060003	SR-23-16-24	16	4	24" - 61	230 mm.	6.00-16" (8PR)	1,77	2,02	1.140	65-70
1011060004	SR-23-16-26	16	4	26" - 66	230 mm.	6.00-16" (8PR)	1,77	2,02	1.225	65-70
1011060005	SR-23-18-24	18	6	24" - 61	230 mm.	6.00-16" (8PR)	2	2,26	1.210	70-75
1011060006	SR-23-18-26	18	6	26" - 66	230 mm.	6.00-16" (8PR)	2	2,26	1.305	70-75
1011060007	SR-23-20-24	20	6	24" - 61	230 mm.	6.00-16" (8PR)	2,23	2,49	1.275	75-80
1011060008	SR-23-20-26	20	6	26" - 66	230 mm.	6.00-16" (8PR)	2,23	2,49	1.380	75-80
1011060009	SR-23-22-24	22	8	24" - 61	230 mm.	10.0/80-12" (8PR)	2,46	2,72	1.520	80-85
1011060010	SR-23-22-26	22	8	26" - 66	230 mm.	10.0/80-12" (8PR)	2,46	2,72	1.635	80-85
1011060011	SR-23-24-24	24	8	24" - 61	230 mm.	10.0/80-12" (8PR)	2,69	2,96	1.535	85-90
1011060012	SR-23-24-26	24	8	26" - 66	230 mm.	10.0/80-12" (8PR)	2,69	2,96	1.660	85-90

## Options



**Additional support point increase (price per unit):**

CODE

2019020004



**Bearing housing protector (price per unit):**

CODE

2019020003



**Increase pneumatic wheel (10,0/75-15,3")**

CODE

2011060001



23 reel rolling assembly