

Olives harvesters with front umbrella

Serie 100

Standard equipment:

- › Control of hydraulic functions of movement through distributor high efficiency calibrated monobloc.
- › Umbrella and clamp opening movement simultaneously.
- › Independent umbrella opening regulation.
- › Front umbrella: from \varnothing 6 to 8 m, lightweight design and reinforced structure.
- › Monomass vibrating heads. System of orbital multiple vibration in both directions to be mounted on the arms of a front-loader. High pressure hydraulic system.
- › Harvesting box.
- › Rear hydraulic central hitched on the 3 points of the tractor, quick hydraulic plugs, counter-weight (in option), visual gauge for the level and temperature of the oil, thermostat, cooling system, suction and return filters.
- › In-cab electronic control box.
- › Quick system to hitch/unhitch quickly the harvesting box.
- › Supplement 5 mass R100
- › PTO SHAFT 1000 r.p.m.
- › Optimal working revolutions: 880 r.p.m.



CODE	MODEL	READY FOR ASSEMBLY IN:	UMBRELLA				POWER (CV)	MINIM. PLANTING DISTANCE (m)*	
			Ø (m)	Fixed	Bass	Folder Hidr.		A	B
1041010015	R100 E	-	6	•	x	x	90	-	-
1041010016	R100 P 7	F	7	•	x	x	100	6	7
1041010017	R100 P 8	F	8	•	x	x	100	7	8
1041010018	R100 PB 6	F	6	x	•	x	100	5	6
1041010019	R100 PB 7	F	7	x	•	x	100	6	7
1041010022	R100 PH 7	F	7	x	x	•	100	6	7
1041010023	R100 PH 8	F	8	x	x	•	100	7	8
1041010021	R100 PH 6 BOBCAT	B	6	x	x	•	90	5	6

F: Front loader | B: Bobcat (Mini-excavator) | • Available | x: Not available | (*) Minimum advisable planting distance

Options




Counter-weight pieces on hydraulic central

CODE
2041010020



400-mm extension of the vibrating head (this option must be mounted in our factory)

CODE
2041010010



Tightening vibrating head adjustment kit

CODE
2041010018



Protection piece of the hydraulic cylinder for R100 (standard in V45)

CODE
2041010006



Increment per joystick for R100

CODE
2041010012



Kit "young olive trees" R100

CODE
2041010016



Kit to guide to the trunk for R100 mounted

CODE
2041010029