

Vibrating head V55 for front high performance olives harvesters

Serie 130. Vibration by closed circuit of pistons

Standard equipment:

- › Control of hydraulic functions of movement by mono-block and distributor of high efficiency.
- › Monomass vibrating heads. System of orbital multiple vibration in both directions to be mounted on the arms of a front-loader. High pressure hydraulic system.
- › Rear hydraulic central hitched on the 3 points of the tractor, quick hydraulic plugs, counter-weight (in option), visual gauge for the level and temperature of the oil, thermostat, cooling system, suction and return filters.
- › In-cab electronic control box.
- › Quick system to hitch/unhitch quickly the harvesting box.
- › Supplement 5 mass 1M.
- › PTO SHAFT 1000 r.p.m.
- › Optimal working revolutions: 880 r.p.m.



CODE	MODEL	VIBR. HEAD EXTENSION (mm)	PUMP CONTROL	VIBR. HEAD	READY FOR ASSEMBLY TO BOX	MINIMUM TRACTOR POWER (CV)
				Protection of cylinder		
1041010040	V55 E	x	Sirga	•	x	120
1041010039	V55	x	Sirga	•	•	120
1041010041	V55 EXT	400	Sirga	•	•	120

• Available | x: Not available

Options



Lateral movement of box and vibrating head

CODE

2041010025



Tightening vibrating head adjustment kit

CODE

2041010019



Increment per joystick

CODE

2049000001



Deck support increment 1M mounted

CODE

2041010002



Increase by self-regulating pump instead of Sirga

CODE

2041010026



Replacement of the standard skirt by soft skirt in equipment 1M

CODE

2041010031



Replacement of standard mallets by mallets with soft clamp in 1M

CODE

2041010030