HARVEST


NUTS HARVESTERS

Dry nuts harvesters with rear umbrella


Serie 90

Standard equipment:

- Simultaneous opening movement of umbrella and vibrating heads.
- Indep. regulation of the fold/ unfold speed of the umbrella.
- > In-cab electronic control box.
- Bimass vibrating head with 1-2 y 1-2-3 mass supplements as standard.
- > Hydraulic central integrated into the harvester.
- > Peelers with independent regulation.
- Hydraulic pipes for unloading endless screw and hydraulic 3rd points directly to the tractor.
- Hitching to the 3 points + connec. Through PTO SHAFT.
- > Protec. Grid for the tractor hydr.Adjustable.
- > Supplement 2 mass.
- > Supplement 3 mass.
- > PTO SHAFT 540 r.p.m.
- > Optimal working revolutions: 380 r.p.m.









	CODE	MODEL	SIST. HIDR. ENGRANES	HYDR. 3rd POINT	HEAD ELEVATION	BOX DIMENSIONS (m)						Ø UMBRELLA (m)	POWER (CV)	MINIM. PLANTING DISTANCE (m)*	
						Adjust. grid	Peelers	а	b	с	d	(11)	(CV)	A	в
	1041070001	RT 65 E	•	х	х	x	х	1,8	3,1	0,65	0,4	6,5	80	5	6
	1041070002	RT 65 P	•	•	•	•	1	1,8	3,1	0,65	0,4	6,5	80	5	6

• Available | x: Not available | (*) Minimum advisable planting distance



HARVEST

NUTS HARVESTERS

Options

